



SANDEN



SANDEN INTERNATIONAL (AUSTRALIA) PTY LTD
 UNIT 6,17 WILLFOX STREET,
 CONDELL PARK,
 NSW 2200

Ph: (02) 9791 0999
Fax: (02) 9791 9029
E-mail: sales@sanden.com.au
Web: www.sanden.com.au

SPECIFICATIONS		SPU-1053	
CABINET	GROSS CAPACITY (LITRES)	1034	
	EXTERNAL DIMENSION (MM)	1020WX700DX2170H	
	INTERNAL DIMENSION (MM)	950WX615DX1770H	
	NET WEIGHT (KGS)	179	
	INSULATION	CYCLOPENTANE	
	DOOR	2 x SELF CLOSING GLASS DOOR FITTED WITH TOUGHENED LOW-E SAFETY GLASS & REPLACEABLE DOOR GASKET	
	NO. OF SHELVES (PCS)	10 X ADJUSTABLE SHELVES WITH TAG HOLDER	
	CASTER WHEEL	4 x NYLON SWIVEL CASTOR	
	ADJUSTABLE LEG	2-ADJUSTABLE LEGS AT FRONT	
	CANOPY LIGHTING (WATTS)	4 x SUPERBRIGHT LED	
	INTERNAL LIGHTING (WATTS)	3 x SUPERBRIGHT LED PER DOOR	
	DRAINAGE	SELF-EVAPORATE	
	COMPRESSOR (HP)	1/3	
REFRIGERATION	REFRIGERANT	R134a	
	EVAPORATOR	FIN & TUBE/ FORCE AIR CIRCULATION	
	EVAPORATOR FAN MOTOR (WATTS)	2 x DC FAN MOTOR	
	CONDENSER	WIRE & TUBE/ FORCE AIR CIRCULATION	
	CONDENSER FAN MOTOR (WATTS)	10	
	POWER SUPPLY	220-240V 50Hz.	
	TEMPERATURE CONTROL	EMS ENERGY MANAGEMENT CONTROLLER	
	DEFROST	OFF - CYCLE	
	COOLING PERFORMANCE	0 ~ +7.2 °C	
	CERTIFICATION	C OF S , C-TICK & MEPS	
GENERAL FEATURE	330ml CAN CAPACITY	FACING	14
		NO. OF CAN	1344
	500ml PET CAPACITY	FACING	14
		NO. OF BOTTLE	672
	UNIT IN CONTAINER	(20 FCL)	17
		(40 FCL)	33
OPTION LIST (ORDER BEFORE PRODUCTION)		<ul style="list-style-type: none"> ● BOTTLE OPENER+RECEPTACLE, ● BACK SIDE GRAPHIC STICKER, ● DIGITAL THERMOMETER, ● VOLTAGE STABILIZER, ● VOLTAGE PROTECTOR, ● EARTH LEAKAGE CIRCUIT BREAKER 	

Specifications subject to change without advance notice.